(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization

International Bureau





(43) International Publication Date 14 October 2004 (14.10.2004)

PCT

(10) International Publication Number WO 2004/088305 A1

(51) International Patent Classification7: 31/10, 27/413, 27/30

G01N 33/18,

(21) International Application Number:

PCT/AU2004/000438

(22) International Filing Date:

5 April 2004 (05.04.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: 2003901589

4 April 2003 (04.04.2003)

(71) Applicant (for all designated States except US): GRIF-FITH UNIVERSITY [AU/AU]; Kessels Road, Nathan, QLD 4111 (AU).

(72) Inventor; and


(75) Inventor/Applicant (for US only): ZHAO, Hujjun

[AU/AU]; 34 Kincaid Drive, Highland Park, QLD 4211 (AU).

- (74) Agent: MISCHLEWSKI, Darryl; IP Strategies, P.O. Box 1254, Camberwell, VIC 3124 (AU).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),

[Continued on next page]

(54) Title: PHOTOELECTROCHEMICAL DETERMINATION OF CHEMICAL OXYGEN DEMAND



(57) Abstract: A method for determining chemical oxygen demand of a water sample comprises the steps of (a) applying a constant potential bias to a photoelectrochemical cell, having a photoactive working electrode (e.g. a layer of titanium dioxide nanoparticles coated on an inert conductive substrate) and a counter electrode, and containing a supporting electrolyte solution; (b) illuminating the working electrode with a light source and recording the background photocurrent produced at the working electrode from the supporting electrolyte solution; (c) adding a water sample, to be analysed, to the photoelectrochemical cell; (d) illuminating the working electrode with a light source and recording the total photoelectrocurrent produced with the sample; (e) determining the chemical oxygen demand according to the type (exhaustive or non-exhaustive) of degradation conditions employed. An apparatus for carrying out the method is also claimed.

WO 2004/088305 A1



Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

with international search report